TECHNICAL BULLETIN SERVICE INFORMATION RETROFIT/UPGRADE



2100 Fernbrook Lane Plymouth, MN 55447-4722 U.S.A.

Phone: 763.553.1270 Fax: 763.553.0459 Toll Free: 1.800.328.3352

Preventative Maintenance for NuAire CO2 Incubators

1. <u>GENERAL MAINTENANCE & CLEANING (PERFORMED PERIODICALLY)</u>

- Clean Exterior: Use a mild detergent and single distilled water as needed.
- Clean Stainless Steel Interior: Wipe down with an appropriate disinfectant such as 70% Isopropyl Alcohol or equivalent non-corrosive disinfectant as necessary. Do not use and Chlorinated or Halogen materials on Stainless Steel.
- For Water Pan: Use only single distilled water. Clean pan and change water on a weekly basis.
 A small amount of Copper Sulfate can be added to the water pan to prevent bacteria growth from occurring.
- > Replace gas supply line filters (CO2 & N2): every fifth tank or when the filter is visibly discolored.
- For Air Inlet Filter: Replace every 3 to 6 months or when the filter is visibly discolored.

2. PREVENTATIVE MAINTENANCE & CALIBRATION (PERFORMED AT MINIMUM EVERY 6 MONTHS):

Perform Preventative Maintenance, Check Incubator and Adjust or Correct as Needed:

- Gas or water leaks.
- > Tubing cracks and tight connections.
- Door switch functionality.
- > All displays & indicator lights working normally.
- > Tank switch functionality (if applicable)
- > Chamber contamination or condensation.
- Pressure settings on gas regulators.
- > Operation of all motors, fan, pumps and heaters.
- > Ability of Incubator to recover to correct gas % within specified time.
- > CO2 sensor and heater operation.
- > Inspect all filters for discoloration and integrity, replace as needed.
- Ensure water level in water jacket is full (if applicable)
- > Inner & outer doors functioning & sealing properly
- All caps in place; (i.e. side access port, RH reservoir & CO2 sample port)

Perform Calibration

- > Chamber temperature calibration.
- ➢ CO2 calibration.
- > Perimeter and door calibration (if condensation is noted on doors and walls)
- > RH calibration (if applicable)
- > O2 calibration (if applicable)

3. PREVENTATIVE MAINTENANCE (PERFORMED EVERY 2 YEARS)

> Replace chamber HEPA Filter of Air-Pump Capsule Filter.