

NU-99579VFT

ULTRALOW TEMPERATURE FREEZER

Refrigeration

PERFORMANCE	
Temperature Range	-40 ~ -86 °C
Cooling Performance	-86 °C
Internal Temp. Uniformity	+/- 3 °C
Internal Temp. Accuracy	0.1 °C
Sound Level	43.5 dBA
Certification	CE, UL, ENERGY STAR®
Cooling Speed (20°C ambient)	
20 °C down to -80 °C	239 minutes
Holdover Time (20°C ambient)	
-80 °C up to -50 °C	245 minutes
1-Minute Door-Open Recovery to -75°C (All Doors Open)	
20 °C ambient	10 minutes
25 °C ambient	40 minutes
Heat Rejection	
At 20 °C ambient	28320 Btu/day
At 25 °C ambient	25591 Btu/day
TECHNOLOGY	
Climate Class	N
Cooling Type	Direct cooling
Compressor(s)	2
Size of Compressor	1 hp
Compressor Capacity	938 W
Refrigerant	HC
Refrigerant Model	R290 / R170
Temperature Sensor	Thermistor Sensor
Controller Sensor	PT100
Defrost Mode	Manual

Capacity

SIZE & FOOTPRINT	
Cabinet Type	Upright
Capacity	579 L / 20.4 ft³
Exterior Dimension	W*D*H 895 * 998 * 1980 mm 35.2 * 39.3 * 78.0 in
Cabinet Width	w/o handle & hinge 800 mm
Door Width	w/o handle 825 mm
Depth	w/o door, w/ drawers 860 mm



Net / Gross Weight	325 / 355 kg 716.5 / 782.6 lb
Interior Dimension	W*D*H 620 * 716 * 1310 mm 24.4 * 28.2 * 51.6 in
Usable Compartment Dimensions	299 / 305 / 305 / 302 mm
Packing Dimension	W*D*H 953 / 1071 / 2127 mm 37.6 / 42.2 / 83.8 in
Container Load	20'/40'/40'H 12 / 24 / 24

STORAGE	
Rack Configuration	5 x 5
Frozen Storage Rack Loading Quantity (2 in)	16
Frozen Storage Box Loading Quantity (2 in)	400
Sample Loading Quantity Calculated at 10 * 10	40000
Shelves	3
Shelf Dimensions	W*D 606 * 650 mm 23.9 * 25.6 in
Shelf Max. Capacity	72 kg / 158.7 lb

Construction

FEATURES	
Cabinet Thickness	90 mm / 3.54 in
Porthole(s)	2
Outer Door	Single Solid Door
Outer Door Thickness	90 mm / 3.54 in
Outer Door Sealing Structure	2 outer sealing strips, 2 layers each (4 layers total)
Padlock Adapter Kit	1
Built-in Key Door Lock	1
Keys	4
Inner Door	Four Solid Doors
Inside Door Sealing Structure	1 inner sealing strip, 1 layer
Shelves / Inner Doors	3 / 4
Adjustable Shelves	Yes
Foot	Yes
Caster	Yes
Caster Count	4
Stop Moving Feet	Yes
MATERIALS	
Exterior Material	Color-coated Cold Plate Steel
Interior Material	Color-coated Steel Plate
Insulation	VIP+CFC-Free Foaming Agent
Shelf Material	Stainless Steel

Electrical

REQUIREMENTS	
Power Supply	100~230 V / 50/60 Hz
Power	1100 W
Max Power Draw	1100 W
Electrical Current	14 A
Power Lead Length	2 m
POWER CONSUMPTION	
Set -70 °C @ 25 °C ambient	6.5 kWh / 24 h
Set -80 °C @ 25 °C ambient	7.5 kWh / 24 h
Set -70 °C @ 20 °C ambient	5.6 kWh / 24 h
Set -80 °C @ 20 °C ambient	8.3 kWh / 24 h
Power Consumption	8.0 kWh / 24 h
OTHER	
5V Power Supply Port	Yes

Control System

INTERFACE	
Display	Touch Screen LCD
Controller Level	TOP
Controller Type	Microprocessor
Temperature Setting Mode	Digital (Min. Accuracy 1° C)
Screen Setting Protection	Yes (Password)
Setpoint Security	Yes
ALARMS & INDICATIONS	
High / Low Temperature	Yes
Adj. High / Low Temperature	Yes
Ambient Temperature Display	Yes
High Ambient Temperature	Yes
Start-up Delay	Yes
Sensor Error	Yes
Power Failure	Yes
High / Low Voltage	Yes
Voltage Exceed	Yes
Filter Dirty	Yes
Hot Condenser	Yes
Door Ajar	Yes
Low Battery	Yes
DATA OUTPUTS	
USB Interface	Yes
Remote Alarm Terminals	Yes
RS232 / 485 Port	NA / Standard
OTHER	
Power Switch	15 A
Backup Battery	Yes
Battery Runtime	22 hours
Temp. Recorder Batt. Runtime	6 hours
Boot Delay Protection	Yes

Accessories

ACCESSORIES	
Temperature Chart Recorder	Optional
CO2 Backup System	Optional
LN2 Backup System	Optional